



Number	KIP0000231C/01	Replaces	KIP0000231C/00
Issued	19/07/2017	First edition	14/07/2017
Report number	IN0000231	Expiry date	18/07/2022
Page	1 of 2		

## Certificate of Type Testing Conformity

**License holder:** Bruk-Bet sp. z o.o.  
Niecieczka 199 - 33-240 Zabno, Poland

**Production site:** Bruk-Bet sp. z o.o.  
ul. Mrozna 8 - 33-102 Tarnow, Poland

**Product:** Photovoltaic (PV) module

**Models:** BEM-325 Wp  
(and extended models)\*

The products can be considered complying to the type testing based upon the following aspects:

- IEC 61215:2005  
Crystalline silicon terrestrial photovoltaic (PV) modules. Design qualification and type approval.  
Test 10.17 – Hail test  
Spheres reference diameter = 55 mm. Spheres reference speed = 33.9 m/sec.

This type testing certificate is only valid for the material combination as listed in the test report. Extended models are based on the tested sample with extension in peak power and with reduction in cell number.\*

This type testing certificate does not include the Initial and the Periodic Inspection of the production samples.

*This certificate is issued in accordance with the Kiwa Cermet Italia regulations for Product Certification. Publication of the certificate is allowed.*

Chief Operating Officer  
Giampiero Belcredi

*Member of the IECCE CB-Scheme*

Kiwa Cermet Italia S.p.A.

Società con socio unico, soggetta all'attività di direzione e coordinamento di Kiwa Italia Holding Srl

Via Cadriano, 23

40057 Granarolo dell'Emilia (BO)

Unità secondaria

Via Treviso 32/34

31020 San Vendemiano (TV)

Tel +39. 0438 411755

Fax +39.0438 22428

E-mail: [info@kiwacermet.it](mailto:info@kiwacermet.it)

[www.kiwa.it](http://www.kiwa.it)

[www.kiwacermet.it](http://www.kiwacermet.it)

Certificate



Number KIP0000231C/01 Replaces KIP0000231C/00  
 Issued 19/07/2017 First edition 14/07/2017  
 Report number IN0000231 Expiry date 18/07/2022  
 Page 2 of 2

# Certificate

## Certificate of Type Testing Conformity


### Annex Extended models\*

(Types extended for similarity without need of re-testing according to IEC61215 "Retesting Guideline")

Model name	Cells number	Cell size (mm)	Cell technology	Module size (mm)	Rated power (Wp)
BEM-XXX Wp	72	156x156	Mono-Si	1960x992	From 260 to 385 with 5 steps
BEM-XXX Wp	60	156x156	Mono-Si	1640x992	From 220 to 320 with 5 steps
BEM-XXX Wp	54	156x156	Mono-Si	1480x992	From 195 to 285 with 5 steps
BEM-XXX Wp	48	156x156	Mono-Si	1320x992	From 175 to 255 with 5 steps
BEM-XXX Wp	36	156x156	Mono-Si	1480x670	From 130 to 190 with 5 steps
BEM-XXX Wp	24	156x156	Mono-Si	1005x670	From 90 to 125 with 5 steps
BEM-XXX Wp	18	156x156	Mono-Si	1470x350	From 65 to 95 with 5 steps
BEM-XXX Wp	12	156x156	Mono-Si	1000x350	From 45 to 60 with 5 steps

Remarks: XXX = rated power. Frame thickness = 40 mm. Module size can vary according to the limits of the IEC61215 Retesting Guideline if the minimum distances between module current carrying part and the edge of the module stay the same.

Chief Operating Officer  
Giampiero Belcredi



Laboratory test report nr.: L0000231/C rev.00.